ethos
FABRICS

Livia

Pictures say more than words. Indoor - Outdoor fabrics for every scenario





Technical specification

Composition:		
Surface	100% Polyester (Solution Dyed)	
Base	100% TPU	
Abrasion test (cycles)	≥ 50.000	
(EN ISO 12947-1+2)	(Martindale)	
Pilling:	Grade 4	
(EN ISO 12945-2)		
Fastness to rubbing dry:	Grade 4-5	
(EN ISO 105-X12)		
Fastness to rubbing wet:	Grade 4-5	
(EN ISO 105-X12)		
Fastness to light:	Grade ≥ 7	
(EN ISO 105 B02)		
Width:	144cm	+/- 2cm
Usable width:	142cm	+/- 2cm
Weight m	710 g/m	+/- 5%
Weight m²	490 g/m²	+/- 5%

ethos
FABRICS

Fabric Finishes:


WATER REPELLENT


STAIN RESISTANT



UV PROTECT




UV RESISTANT


EASY TO CLEAN



SOFT


MOULD RESISTANT

Recommended care labeling:




WASH 30°


TUMBLE DRY


IRON


DRY CLEAN


BLEACHING


AIR DRY

“Characteristic material properties”

Slight variations in color and structure between different batches are due to production techniques. Woven fabrics may occasionally have small thickened threads or inclusions—these are not defects, but signs of the weaving process.

With daily use, flat fabrics naturally become slightly rougher, and depending on the material, a slight striping effect may become visible. Protect the fabric from sharp objects or Velcro fasteners to prevent thread pulling. The formation of small knots (pilling) is a normal characteristic of use and can also be caused by external fibers."

Ethos Fabrics B.V. I Nijverheidsweg 1 I 7442 CH Nijverdal I The Netherlands
www.ethosfabrics.com